

GENERAL INFORMATION

Unit: mm (in)

FRONT WHEEL/SUSPENSION/STEERING		STANDARD	SERVICE LIMIT
ITEM			
Minimum tire tread depth			1.5 (0.06)
Cold tire pressure	Drive only	250 kPa (2.50 kgf/cm ² , 36 psi)	
	Driver and passenger	250 kPa (2.50 kgf/cm ² , 36 psi)	
Axle runout			0.20 (0.008)
Wheel rim runout	Radial		2.0 (0.08)
	Axial		2.0 (0.08)
Fork	Spring free length	320.5 (12.62)	314.1 (12.37)
	Spring direction	With the tapered end facing down	
	Tube runout		0.20 (0.008)
	Recommended fork fluid	Fork fluid	
	Fluid level	164 (6.5)	
	Fluid capacity	446 ± 2.5 cm ³ (15.1 ± 0.08 US oz, 15.7 ± 0.09 Imp oz)	
Steering head bearing pre-load		10 – 15 N (1.0 – 1.5 kgf)	

Unit: mm (in)

REAR WHEEL/SUSPENSION		STANDARD	SERVICE LIMIT
ITEM			
Minimum tire tread depth			2.0 (0.08)
Cold tire pressure	Driver only	290 kPa (2.90 kgf/cm ² , 42 psi)	
	Driver and passenger	290 kPa (2.90 kgf/cm ² , 42 psi)	
Axle runout			0.20 (0.008)
Wheel rim runout	Radial		2.0 (0.08)
	Axial		2.0 (0.08)
Drive chain	Size/link	DID	DID50ZV-110LE
		RK	RK50LFO-110LE
	Slack	25 – 35 (1.0 – 1.4)	50 (2.0)
Shock absorber	Spring adjuster standard position	3rd groove	