

FRONT WHEEL/SUSPENSION/STEERING SPECIFICATIONS

Unit: mm (in)

ITEM		STANDARD	SERVICE LIMIT
Minimum tire tread depth		-	To the indicator
Cold tire pressure	Driver only	175 kPa (1.75 kgf/cm ² , 25 psi)	-
	Driver and passenger	175 kPa (1.75 kgf/cm ² , 25 psi)	-
Axle runout		-	0.2 (0.01)
Wheel rim runout	Radial	-	2.0 (0.08)
	Axial	-	2.0 (0.08)
Fork	Spring free length	218.0 (8.58)	213.6 (8.41)
	Pipe runout	-	0.2 (0.01)
	Recommended fluid	Fork fluid	-
	Fluid level	52 (2.0)	-
	Fluid capacity	89.0 ± 1.0 cm ³ (3.01 ± 0.03 US oz, 3.13 ± 0.04 Imp oz)	-

REAR WHEEL/SUSPENSION SPECIFICATIONS

Unit: mm (in)

ITEM		STANDARD	SERVICE LIMIT
Minimum tire tread depth		-	To the indicator
Cold tire pressure	Driver only	200 kPa (2.00 kgf/cm ² , 29 psi)	-
	Driver and passenger	225 kPa (2.25 kgf/cm ² , 33 psi)	-
Wheel rim runout	Radial	-	2.0 (0.08)
	Axial	-	2.0 (0.08)

BRAKE SYSTEM SPECIFICATIONS

Unit: mm (in)

ITEM		STANDARD	SERVICE LIMIT
Front disc brake	Specified brake fluid	DOT 3 or DOT 4	-
	Brake disc thickness	3.3 – 3.7 (0.13 – 0.15)	3.0 (0.12)
	Brake disc warpage	-	0.30 (0.012)
	Master cylinder I.D.	12.700 – 12.743 (0.5000 – 0.5017)	12.755 (0.5022)
	Master piston O.D.	12.657 – 12.684 (0.4983 – 0.4994)	12.645 (0.4978)
	Caliper cylinder I.D.	27.000 – 27.050 (1.0630 – 1.0650)	27.060 (1.0654)
	Caliper piston O.D.	26.918 – 26.968 (1.0598 – 1.0617)	26.91 (1.059)
Rear drum brake	Brake lever freeplay	10 – 20 (0.4 – 0.8)	-
	Brake drum I.D.	130.0 – 130.2 (5.12 – 5.13)	131.0 (5.16)