

<p>Adjustable remover shaft 07JAC-PH80200</p> 	<p>Remover weight 07741-0010201</p> 	<p>Attachment, 44 x 49.5 mm 07945-3330300</p> 
---	---	---

TROUBLESHOOTING

Hard steering

- Insufficient tire pressure
- Faulty tire
- Steering stem adjusting nut too tight
- Faulty steering head bearing
- Faulty steering head bearing race
- Bent steering stem

Steers to one side or does not track straight

- Bent front axle
- Wheel installed incorrectly
- Worn or damaged front wheel bearings
- Bent fork
- Worn or damaged engine mounting bushings (page 8-6)
- Bent frame
- Faulty steering head bearing

Front wheel wobbles

- Loose front axle fasteners
- Bent rim
- Worn or damaged front wheel bearings

Front wheel turns hard

- Front brake drag
- Bent front axle
- Faulty front wheel bearings

Soft suspension

- Low tire pressure
- Deteriorated fork fluid
- Incorrect fork fluid viscosity
- Insufficient fluid in fork
- Weak fork spring

Hard suspension

- High tire pressure
- Too much fluid in fork
- Incorrect fork fluid viscosity
- Bent fork pipes
- Clogged fork fluid passage

Suspension noisy

- Worn fork slider guide bushing
- Insufficient fluid in fork
- Loose fork fasteners